



## WALL / FLOOR BRACKET

For added security and safety:

- 1) It is strongly recommended that all cabinets be secured to the floor or wall.
- 2) The Bracket provided maybe used to secure the cabinet to the floor or wall.
- 3) **You may substitute other hardware to meet your specific mounting needs.**
- 4) For securing the cabinet to the floor:
  - A. Place the cabinet in its desired location and adjust leveling feet if needed.
  - B. Place the bracket around the two rear legs of the cabinet.
  - C. Most cabinets have factory drilled pilot holes, if your cabinet does not then drill two 7/64" pilot holes into the rear legs of the cabinet stand.
  - D. Secure the bracket to the stand using two sheet metal screws.
  - E. Secure the bracket to the floor with at least two wood screws or other appropriate hardware.
- 5) For securing the cabinet to the wall:
  - A. Place the cabinet in the desired location, no more than 3 ½" from the wall (for the provided hardware) and adjust the leveling feet if needed.
  - B. The bracket maybe attached to the Top rear of the cabinet.
  - C. If your cabinet does not have predrilled pilot holes then it will be necessary for you to drill the pilot holes in the upper rear portion of both side panels. The holes should be located approximately 3/8" down from the top and in from the rear of the cabinet.
  - D. Locate a solid surface on the wall for the bracket to be secured to. (Wall stud or wood etc.)
  - E. Place the bracket against the solid surface and the cabinet and secure the bracket to the wall using at least two wood screws or other appropriate hardware.
  - F. Secure the bracket to the cabinet using two sheet metal screws.

**\*\* Other hardware maybe used (different brackets, nylon straps, wall anchors etc.) to secure the cabinets to the wall or floor depending on your specific mounting requirements. In all cases the mounting hardware that is used to mount into the cabinet should not be located more that 3" from the rear edge of the cabinet and must not extend into the cabinet more than ½". \*\***

**If you should have any questions concerning these mounting instructions or any questions with regard to our product please contact our customer service: Static Safe® Products company: Toll Free at 1-866-937-6391**